

BETO circle

suspended

EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; extremely slim design (only 42 x 42 mm); surface powder coated; pendant fitting with cable suspension; height adjustment without tools; with transparent feeder cable; electronic operating unit installed in the canopy; extruded profile for improved thermal management; high-gloss reflector with faceted design; direct or direct/indirect light distribution; indirect light component with integrated PC boards and high-quality lens system for maximum, homogeneous ceiling illumination; energy-efficient LEDs with very good colour rendering


FR Corps de luminaire en forme d'anneau en profil extrudé roulé en aluminium soudé sans trace visible ; forme extrêmement élancée (seulement 42 x 42 mm) ; surface thermolaquée ; suspension par câble ; réglage en hauteur sans outil ; conduit d'alimentation transparent inclus ; disp. électronique d'alimentation intégré au cache-piton ; profil extrudé pour une meilleure gestion de la température ; réflecteur ultra-brillant avec optique à facettes ; caractéristique de rayonnement direct ou direct / indirect ; dispositif de lumière indirecte avec platines dédiées et optique de lentille de grande qualité pour un éclairage de plafond homogène maximal ; LED économes en énergie à restitution de couleur élevée

Quickinfo

3000 K, 4000 K, TW
 CRI ≥ 80, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 up to 158 lm/W
 L90 @ 50000h
 DALI-2
 reflector (UGR ≤ 19)

Types


suspended




Colours



Light distributions



DIN EN 12464-1
 UGR ≤ 19



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE

3000K	5
4000K	6
tunable white 2700–6500K*	D

*DALI-2 DT8

CONTROL

DALI-2

MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8

LIGHT OPTIC COLOUR

chrome reflector	R
black reflector	B

LIGHT OPTIC COVER

reflector (UGR ≤ 19)



Options on request

COLOUR RENDERING INDEX



CRI ≥ 90
CRI ≥ 98 XPECTRUM

CONTROL

Casambi



*tunable white version



*tunable white and direct/indirect power version

BETO circle 800 suspended



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
46 W	3000 K	6420 lm	0 7 4 - 7 4 0 3 :: 3 ■ ■
	4000 K	7080 lm	



DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
93 W	3000 K	↓ 5500 / ↑ 7100 lm	0 7 4 - 7 4 4 3 :: 3 ■ ■
	4000 K	↓ 6070 / ↑ 7830 lm	

BETO circle 1600 suspended



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
93 W	3000 K	12800 lm	0 7 4 - 7 4 0 4 :: 3 ■ ■
	4000 K	14200 lm	




DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
175 W	3000 K	↓ 12800 / ↑ 12200 lm	0 7 4 - 7 4 4 4 :: 3 ■ ■
	4000 K	↓ 14200 / ↑ 13500 lm	

tunable white on request

Light distribution



reflector (UGR ≤ 19)
direct/indirect power

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, reflector chrome;
reflector black -29%