

## INO square suspended


**EN** Square aluminium luminaire housing; surface powder coated; pendant fitting with cable suspension; height adjustment without tools; with transparent feeder cable; electronic operating unit installed in the canopy; completely homogeneously illuminated, satinated PMMA cover; inwards facing emission characteristics; direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; canopy with 2 cable openings and plug-in terminal for through wiring

**ES** Cuerpo cuadrado de aluminio; superficie con recubrimiento de pintura en polvo; suspendido con cable; altura regulable sin herramientas; incl. cable de alimentación transparente; driver instalado en el baldaquino; tapa PMMA iluminada homogéneamente con acabado sanitado; proyección orientada hacia el interior; iluminación directa/indirecta con un alto confort visual; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino con abertura de 2 orificios para integrar el cableado y sencilla conexión terminal

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI ≥ 90, 3 SDCM  
 up to 120 lm/W  
 L90 @ 50 000 h  
 DALI-2  
 opal


### Types



### Colours




### Light distribution




DiiA® standards  
251, 252, 253



direct/indirect  
illumination



tunable white  
2700–6500 K



CRI ≥ 98  
XPECTRUM

### Order options

**SUSPENSION**  
 cable 2000 mm / canopy central

COLOUR TEMPERATURE	
2700 K	4
3000 K	5
4000 K	6

### CONTROL

DALI-2

### MATERIAL COLOUR

○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours* ● p. 992	X

\*canopy always in white

### LIGHT OPTIC COVER

opal high performance

### Options on request

#### SUSPENSION

cable 2000 mm

#### COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

#### CONTROL

Casambi

#### COLOUR TEMPERATURE


tunable white 2700–6500 K

DALI-2 DT8

#### SHAPES


INO trig suspended  
 INO hex suspended  
 INO circle vertical suspended

### Light distribution



opal high performance  
 direct/indirect

**LUMINOUS FLUX** value calculated for  
 CRI ≥ 90, colour white, cover opal




### INO 750 square suspended




#### DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
39 W	2700 K	4230 lm	0 3 4 - 4 4 4 2 :: 3 H
	3000 K	4450 lm	
	4000 K	4670 lm	




### INO 1000 square suspended



#### DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
52 W	2700 K	5640 lm	0 3 4 - 4 4 4 3 :: 3 H
	3000 K	5930 lm	
	4000 K	6220 lm	




### INO 1250 square suspended



#### DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
65 W	2700 K	7060 lm	0 3 4 - 4 4 4 4 :: 3 H
	3000 K	7420 lm	
	4000 K	7780 lm	



### INO 1500 square suspended



#### DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
79 W	2700 K	8480 lm	0 3 4 - 4 4 4 5 :: 3 H
	3000 K	8920 lm	
	4000 K	9340 lm	