

SPADO 100/150

recessed

EN Round or square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; choice of symmetric or asymmetric (only SPADO 150 round trim) radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system


FR Corps de luminaire rond ou carré en aluminium moulé ; avec bord continu ; convient aux épaisseurs de plafond de 2-25 mm ; surface thermolaquée ; montage sans outil avec fermeture par ressort à déclic ; réflecteur en polycarbonate, chromé brillant ; au choix avec caractéristiques de rayonnement symétriques ou asymétriques (uniquement SPADO 150 round trim) ; niveau de luminaire en retrait ; LED économes en énergie à restitution de couleur élevée ; convertisseur externe pour fente plafond, câblage continu adapté ; ballast approprié pour le fonctionnement sur un système de batterie centrale

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 118 lm/W
L90 @ 50 000 h
non DIM, DALI-2
‡ IP44/† IP20

Types

SPADO 100



SPADO 150

asymmetric



Colours



Light distributions



DiiA® standards
251, 252, 253



glare control
(UGR ≤ 19)



splash water
protection (IP44)

Order options

COLOUR TEMPERATURE	☐☐
3000K	5
4000K	6

CONTROL	⬆️⬆️
non DIM	1
DALI-2	3


MATERIAL COLOUR	☑️
☐ traffic white RAL 9016	7
● jet black RAL 9005	8

Options on request

COLOUR TEMPERATURE	
2700K	

MOUNTING SET

acoustic soft ceilings
only for SPADO 100 round trim




SPADO 100 round trim



DOWNLIGHT (⚡ IP 44/± IP 20)

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
9.3 W	990 lm	0 4 9 - 3 1 1 1 ☐☐☐☐☐☐




SPADO 150 round trim




DOWNLIGHT (⚡ IP 44/± IP 20)

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
16.4 W UGR ≤19	1940 lm	0 4 9 - 3 1 2 1 ☐☐☐☐☐☐
27.5 W	3130 lm	0 4 9 - 3 1 2 3 ☐☐☐☐☐☐




SPADO 150 round trim



WALLWASHER ASYMMETRIC (⚡ IP 44/± IP 20)

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
10.7 W	944 lm	0 4 9 - 3 1 2 2 ☐☐☐☐☐☐



SPADO 150 square trim



DOWNLIGHT (⚡ IP 44/± IP 20)

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
16.4 W UGR ≤19	1910 lm	0 4 9 - 3 1 5 1 ☐☐☐☐☐☐
27.5 W	3170 lm	0 4 9 - 3 1 5 2 ☐☐☐☐☐☐

Mounting accessories


EXPOSED CONCRETE CEILINGS

TYPE	L-W-H (mm)	ORDER CODE
SPADO 150 round	295-295-160	0 4 9 - 3 1 9 1 2 1 0
SPADO 150 square	400-260-160	0 4 9 - 3 1 9 2 2 1 0

PRIMED CONCRETE CEILINGS

TYPE	Ø-H (mm)	ORDER CODE
SPADO 150 round/square	307-170	0 4 9 - 3 1 9 1 4 1 0

Light distribution



SPADO 150 asymmetric

LUMINOUS FLUX value calculated for
4000K, colour white, reflector chrome
3000K -5%