

SPADO 100/150

recessed

EN Round or square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; choice of symmetric or asymmetric (only SPADO 150 round trim) radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system


IT Corpo illuminante rotondo o quadrato in pressofusione di alluminio; con bordo perimetrale; per soffitti di spessore 2-25 mm; verniciatura a polvere; montaggio senza utensili con chiusura a molla a scatto; riflettore in policarbonato, cromo lucido; a scelta con emissione simmetrica o asimmetrica (solo SPADO 150 round trim); superficie di emissione arretrata; LED ad efficienza energetica con elevata resa cromatica; converter esterno da inserire nel soffitto, cablaggio passante adatto; alimentatore compatibile con funzionamento a batteria centrale

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 118 lm/W
L90 @ 50 000 h
non DIM, DALI-2
‡ IP44/† IP20


Types

SPADO 100



SPADO 150

asymmetric



Colours



Light distributions



DiiA® standards
251, 252, 253



glare control
(UGR ≤ 19)



splash water
protection (IP44)

