




Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 up to 4300lm/m
 up to 138lm/W
 L90 @ 50000h
 non DIM, DALI-2
 opal

Types



Colour



Light distributions



TUBO 100 system


surface/suspended

EN Supporting profile in extruded aluminium; end cap in aluminium, no visible screws; for lighting systems; powder coated; luminaire profile for mounting available in advance; remaining components mounted without tools; surface mounted or suspended luminaire with cable suspension; height adjustment without tools; spring clip attachment to the luminaire; freely positionable; with transparent feeder cable; light inset consisting of highly reflective coated extruded profile for improved thermal management; cylindrical cover made of satinised PMMA for homogeneous illumination; with 340° light emission and light ceiling illumination; energy-eff. LEDs – very good colour rendering

ES Perfil soporte fabricado en aluminio; tapas finales de aluminio sin tornillos visibles; para sistemas de iluminación; recubierto de polvo; Perfil disponible para pre-montaje; los demás componentes se pueden montar sin herramientas; lámpara superpuesta o lámpara colgante con cable; altura regulable sin herramientas; fijación en las lámparas por medio de enganches elásticos; ajustable de una manera sencilla; incl. cable de alimentación transparente; elemento de luz formado por perfil extruido con acabado altamente reflectante para una gestión térmica mejorada; cubierta cilíndrica de PMMA satinada para iluminación homogénea; con 340° de emisión e iluminación de techo; LED energét. efíc. – excelente reprod. crom.



single luminaire
(p. 576)



uniform
illumination

Order options

| COLOUR TEMPERATURE | |
|--------------------|---|
| 3000K | 5 |
| 4000K | 6 |

| CONTROL | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

MATERIAL COLOUR

pure white RAL 9010

Options on request

CONTROL



Casambi

EMERGENCY LIGHT

1h Accupack

3h Accupack

only available for length 1463mm



TUBO 100 ceiling/suspended

INSTALLATION CHANNEL

| TYPE | L (mm) | ORDER CODE |
|----------------------|--------|----------------|
| installation channel | 582 | 0 29-00667 |
| installation channel | 882 | 0 29-00967 |
| installation channel | 1182 | 0 29-01267 |
| installation channel | 1482 | 0 29-01567 |
| installation channel | 2364 | 0 29-02567 |
| installation channel | 3000 | 0 29-03067 |
| installation channel | custom | E 85950 ···· 7 |

LIGHT OPTIC COVER OPAL HIGH PERFORMANCE

| TYPE | L (mm) | ORDER CODE |
|-------------------|--------|-----------------|
| light optic cover | 577 | 006-5205700 |
| light optic cover | 877 | 006-5208700 |
| light optic cover | 1177 | 006-5211700 |
| light optic cover | 1477 | 006-5214700 |
| light optic cover | 2359 | 006-5223400 |
| light optic cover | 2995 | 006-5230000 |
| light optic cover | custom | E 85910 ···· 00 |

LIGHT INSET

| SYSTEM POWER | L (mm) | ORDER CODE |
|--------------|--------|------------------|
| 18.3W | 571 | 0 29-8832 ···· 7 |
| 27.5W | 871 | 0 29-8833 ···· 7 |
| 37W | 1171 | 0 29-8834 ···· 7 |
| 46W | 1463 | 0 29-8835 ···· 7 |
| 73W | 2341 | 0 29-8838 ···· 7 |

| COVER | COLOUR TEMP. | SYSTEM POWER | DELIVERED LUMENS | EFFICACY |
|-------------|--------------|--------------|------------------|----------|
| opal high | 3000K | 31W/m | 4060lm/m | 131lm/W |
| performance | 4000K | | 4300lm/m | 138lm/W |

Accessories

END CAPS

| TYPE | ORDER CODE |
|-----------------|------------|
| end caps (pair) | 0 29-14067 |

LINEAR CONNECTOR

| TYPE | ORDER CODE |
|----------------------------------|-----------------|
| linear connector (1 piece) | 0 29-12027 |
| linear connector (10 pieces) | 0 29-12027 . 10 |
| opal cover linear connector | 0 29-12927 |
| anti-slip protection (per cover) | 0 29-00347 |

MOUNTING

| TYPE | L (mm) | ORDER CODE |
|--|--------|-------------|
| ceiling mounting set | 40 | 0 29-00446 |
| cable suspension | 1500 | 005-2142110 |
| angular cable susp. (max. 60°) | 1500 | 005-2142210 |
| canopy/feeder cable 3 × 1.5mm ² | 1500 | 005-2222317 |
| canopy/feeder cable 5 × 1.5mm ² | 1500 | 005-2222417 |
| cable rail | 1200 | 005-2491110 |

for electrical system configuration see luminaire data sheet at xal.com

THROUGH WIRE

| TYPE | ORDER CODE |
|---|------------|
| 3 × 1.5mm ² (non DIM, 10 pieces) | 004-90003 |
| 5 × 1.5mm ² (DALI-2, 10 pieces) | 004-90005 |

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, cover opal