



## TUBO 60

surface / suspended


EN Supporting profile in extruded aluminium; end cap in aluminium; surface powder coated; suitable for wall or ceiling mounting (TUBO 60 surface); surface mounted or suspended luminaire with cable suspension; height adjustment without tools; with feeder cable; light control via high-quality lens system for maximum, homogeneous illumination; completely homogeneously illuminated, cylindrical HPO (High Performance Opal) cover; energy-efficient LEDs with very good colour rendering

▮ Binario portante in profilo di alluminio estruso; testata di chiusura in alluminio; verniciatura a polvere; per montaggio a parete o soffitto (TUBO 60 surface); corpo illuminante a plafone o sospensione con fune; regolazione altezza senza utensili; con cavo di alimentazione; controllo della luce con ottica lenticolare di alta qualità per un'illum. omogenea; cover cilindrica HPO (High Performance Opal) illuminata in modo perfett. omogeneo; LED ad efficienza energetica con elevata resa cromatica

### Quickinfo

3000 K, 4000 K  
CRI ≥ 80, 3 SDCM  
up to 114 lm/W  
L90 @ 50000 h  
DALI-2  
opal

### Types




### Colours




### Light distributions



driver integrated



system solution (p. 952)



uniform illumination


### Order options

<b>COLOUR TEMPERATURE</b>	☼☼
3000K	5
4000K	6


<b>CONTROL</b>	
DALI-2	

<b>MATERIAL COLOUR</b>	☑
○ pure white RAL 9010	7
● jet black RAL 9005	8

<b>LIGHT OPTIC COVER</b>	
opal	




### TUBO 60 surface




#### LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
16.5 W	3000K	1780lm	625	0 5 8 - 3 1 1 2 :: 3 ☑ O
	4000K	1880lm		
33 W	3000K	3560lm	1210	0 5 8 - 3 1 1 4 :: 3 ☑ O
	4000K	3760lm		
37 W	3000K	4130lm	1500	0 5 8 - 3 1 1 5 :: 3 ☑ O
	4000K	4290lm		
66 W	3000K	7110lm	2375	0 5 8 - 3 1 1 8 :: 3 ☑ O
	4000K	7530lm		




### TUBO 60 suspended



#### LUMINAIRE

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
16.5 W	3000K	1780lm	625	0 5 8 - 3 2 1 2 :: 3 ☑ O
	4000K	1880lm		
33 W	3000K	3560lm	1210	0 5 8 - 3 2 1 4 :: 3 ☑ O
	4000K	3760lm		
37 W	3000K	4130lm	1500	0 5 8 - 3 2 1 5 :: 3 ☑ O
	4000K	4290lm		
66 W	3000K	7110lm	2375	0 5 8 - 3 2 1 8 :: 3 ☑ O
	4000K	7530lm		

### Light distribution



opal  
direct

**LUMINOUS FLUX** value calculated for  
CRI ≥ 80, colour white, cover opal